





SPECIFICATIONS


Capacity	30,000lbs @ 4ft							
Boom Length	92ft							
Retracted Length	28ft (Low profile stowed position)							
Tip Height	102ft							
Outriggers	4 (Out & Down, Self-Leveling)							
Outrigger Controls	Operator's Cab & Ground Leve							
True 2-Speed Winch	12,000lb Single-Line pull							
Winch Controls	In-Cab Anti-2 Block Winch Control							
Overload System	LMI Overload Operator Display							
Hydraulic Controls	Joystick or Paddle - Pulse with Modulation							
Swing Design	360° Continuous Rotation							
Warranty	12 Months - Parts/Labor							

- Can be Mounted on Your Choice of Truck
- The Most Advanced LMI System offered on any New Crane
- Outrigger Controls at Operator Seat and Ground Level
- Custom Tailored Paint to Match Your Company Colors

- Wireless 4-Function Remote Control
- Work Baskets

LOAD CHARTS

LOAD RATINGS WITH ALL OUTRIGGERS FULLY EXTENDED													
WORKING RADIUS	28FT BOOM		39FT BOOM		49FT BOOM		59FT BOOM		71FT BOOM		92FT BOOM		
FT	LOADED BOOM ANGLE	LBS	LOADED BOOM ANGLE	LBS	LOADED BOOM ANGLE	LBS	LOADED BOOM ANGLE	LBS	LOADED BOOM ANGLE	LBS	LOADED BOOM ANGLE	LBS	
4	81°	30000											
5	78°	23500											
8	72°	16300	77°	13800	80°	13800							
10	67°	13700	75°	13000	78°	12600	81°	12300					
12	63°	11700	71°	11100	76°	10700	79°	10500	81°	9100			
15	55°	9700	66°	9150	71°	8750	75°	8500	78°	7400			
20	42°	7150	59°	6950	66°	6700	71°	6400	74°	5800	79°	5000	
25			49°	5300	59°	5200	65°	5100	70°	4500	76°	4000	
30			38°	4100	52°	4100	60°	4100	65°	3750	73°	3200	
35			23°	3200	44°	3200	54°	3200	61°	3150	69°	2650	
40					34°	2600	47°	2600	56°	2600	66°	2200	
45					20°	2100	40°	2100	50°	2100	62°	1800	
50							31°	1700	45°	1700	58°	1500	
55							19°	1350	38°	1350	55°	1250	
60									31°	1100	51°	1050	
65									21°	900	46°	900	
70											41°	750	
75											37°	650	
80											31°	550	



NATIONWIDE RENTALS | SALES | SERVICE | FINANCING AVAILABLE



